

SS Seal-Grip

Technical Data Sheet (09/6/13) BLEACHED ALUMINUM OXIDE FOR CONCRETE



PRODUCT DESCRIPTION

SS Seal-Grip is a bleached aluminum oxide that acts as a slip resistant aggregate when added to sealers or coatings. This product is a longer lasting slip resistant making it an excellent choice when needing extra protection against slick concrete.

SS Seal-Grip comes in three different aggregate sizes, 36, 60 and 80.

BENEFITS AND FEATURES

- Excellent long term wear capabilities.
- Great for outdoor use around the pool or any surface area that needs protection from slipping.
- Can be used indoor or out.

RECOMMENDED APPLICATIONS

SS Seal-Grip is perfect for any area needing slip resistance such as pool decks, auto service centers, warehouses, mud rooms, laboratories, aircraft hangars, etc.

PACKAGING

Each particle size is available in 4 oz., quart, or 50 pound bag.

APPROXIMATE COVERAGE RATES

Start with one tablespoon per gallon. Always do a test for each application.

INSTRUCTION FOR USE

DIRECTIONS: Roll out sealer or coating of choice. Hand broadcast SS Seal-Grip. Back roll with more sealer to insure coverage and to encapsulate the particles.

CLEAN UP

Consult Tech Data Sheet for the sealer used.

PRODUCT REMOVAL

N.A.

SHELF LIFE

SS Seal Grip has an unlimited shelf life in it's original, sealed, unopened container.

SPECIAL NOTES

Please consult Material Safety Data Sheet (MSDS) prior to use. This information can be requested by contacting customer service at 866-906-2006.



www.ssspecialtiesconcrete.com

Distributed by Cimarron Wholesale | 125 NE 40th Street | Oklahoma City, OK 73105 USA | Phone 866-906-2006 | Fax 405-526-2008

SealGrip
09/06/13