

SS Xylene



Technical Data Sheet (05/19/16)

RAW SOLVENT FOR CLEANUP, THINNING AND RE-EMULSIFICATION

PRODUCT DESCRIPTION

SS Xylene is used in various aspects of the decorative concrete industry. SS Xylene as well as mineral spirits and acetone are used in the paint and coatings manufacturing process. This solvent can be used for many various reasons such as paint and coating, clean-up for tools and accessories, paint thinning, coating re-emulsification for purpose of fixing faulty applications or conditions, etc.

BENEFITS AND FEATURES

- Superior cleaning capabilities and re-emulsification properties of solvent based coatings.
- Quick drying thinner.
- Pure virgin solvent.

RECOMMENDED APPLICATIONS

Applications vary.

TECHNICAL INFORMATION

Solids	0%
Drying Time	0.86 (Evaporation Rate)
Re-Coat Time.....	n/a
Foot Traffic.....	n/a
Wheel Traffic	n/a
Application Temp.....	50°F—80°F
Wet Appearance	Clear
Dry Appearance	n/a
VOC Content	Exempt
Blush Resistance	n/a
Solvent Resistance	n/a
Concrete Adhesion	n/a

Please note that low air and/or concrete temperatures and/or relative humidity may extend drying times. Follow recommended coverage rates for best results.

SPECIFICATIONS/COMPLIANCES

Not applicable.

APPROXIMATE COVERAGE RATES

Coverage rates vary depending upon surface porosity and texture, and application method. Follow directions for best results.

INSTRUCTION FOR USE

Instructions vary due to extensive amount of uses. Please contact the manufacturer for details pertaining to specific application.

CLEAN UP

Dispose of containers in accordance with local and federal regulations.

PRODUCT REMOVAL

Not applicable.

SHELF LIFE

SS Xylene has a shelf life up to one or two years in its original, sealed, unopened container.

PACKAGING

SS Xylene is packaged in 1 quart cans, 1 gallon cans and 5 gallon pails. Bulk sizes available upon request.

PRECAUTIONS AND LIMITATIONS

- Keep away from open flames. SS Xylene is flammable and is very susceptible to ignition. (Flash point <80°F)
- SS Xylene will not freeze during storage, however, allow temperature to rise to 50°F prior to application.
- All HVAC ventilation ducts should be somehow blocked prior to application so solvent fumes are not distributed. It is recommended to turn OFF the HVAC system.
- Coverage rates depend upon many conditions including application method, surface porosity, applicator, etc.
- SS Xylene can revitalize heavily coated, old, and deteriorated concrete sealer applications.
- SS Xylene does not make existing coatings resistant to brake fluid, gasoline, and many similar products.

SPECIAL NOTES

Please consult Safety Data Sheet (SDS) and read Warranty information prior to use. This information can be requested by contacting customer service at 866-906-2006.

WARRANTY

SS Specialties and its affiliates warrant our products to be of good quality, free of defects and will conform to our published specification in force on the date of acceptance of the order. As the exclusive remedy for breach of this warranty, SS Specialties will replace defective materials ninety days after SS Specialties has shipped the product. All our warranty and other duties with respect to the quality of materials delivered shall conclusively be presumed to have been satisfied, all liability therefore terminates, and no action for breach of any said duties may thereafter be commenced. No warranty is expressed or implied as to the length of life of this product or merchantability or fitness. Liability, if any, is limited to the purchase price of the material. Under no circumstances will SS Specialties be liable for any consequential damages in excess of the purchase price of the product.



www.ssspecialtiesconcrete.com

Distributed by SS Specialties | 121 NE 40th Street | Oklahoma City, OK 73105 USA | Phone 866-906-2006 | Fax 405-526-2008

Xylene
05/19/16