

enFORCE

Technical Data Sheet (01/31/14) HEAVY DUTY FIBER



PRODUCT DESCRIPTION

enFORCE is especially formulated to be used with enCOUNTER, the professional concrete countertop system. When enFORCE is used in conjunction with enFLOW the enCOUNTER Mix conveniently conforms to any pre-casting surface leaving an extremely smooth and abrasion resistant surface. enFORCE is an extra heavy-duty fiber offering maximum long term durability with structural enhancements yet will not change the surface appearance after demolding.

BENEFITS AND FEATURES

- Non-corrosive
- Non-magnetic
- Non-metallic
- 100% alkali proof

RECOMMENDED APPLICATIONS

enFORCE is ideal for use in thin wall applications where rebar or wire is not an option. When used in longer countertops enFORCE add considerable strength and is ideal when the top is cantilevered.

DIRECTIONS FOR USE

Introduce enFORCE into a barrel style mixer either by handfuls or by the complete bag at any time during the mixing process. Allow sufficient time for the fibers to disperse. If bundles of enFORCE do not disperse it may become necessary to shut the mixer down and manually breakup the balls of enFORCE and continue mixing

LIMITATIONS

- enFORCE is designed to reinforce molded concrete or upside down casting. The texture of the fiber will challenge even the most skilled finisher in a cast-up application.

- Contact SS Specialties (866-906-2006) for additional reinforcement methods and products which may be more suitable for cast-up applications.
- The statements made within this technical data sheet, SDS, product labels, etc are guidelines only. The end user should always perform tests and product evaluations prior to application to ensure suitability for particular uses.

SHELF LIFE

enFORCE has an indefinite shelf life.

PACKAGING

enFORCE is packaged in water disposable bags conveniently sized to dose 4 bags of enCOUNTER.

SPECIAL NOTES

Please consult Safety Data Sheet (SDS) and read Warranty information prior to use. This information can be requested by contacting customer service at 866-906-2006.

WARRANTY

SS Specialties warrants our products to be of good quality, free of defects and will conform to our published specification in force on the date of acceptance of the order. As the exclusive remedy for breach of this warranty, SS Specialties will replace defective materials ninety days after SS Specialties has shipped the product, all our warranty and other duties with respect to the quality of materials delivered shall conclusively be presumed to have been satisfied, all liability therefore terminates, and no action for breach of any said duties may thereafter be commenced. No warranty is expressed or implied as to the length of life of this product or merchantability or fitness. Liability, if any is limited to the purchase price of the material under no circumstances will SS Specialties be liable for a consequential damage to any in excess of the purchase price of their product..



www.ssspecialtiesconcrete.com

Distributed by Cimarron Wholesale | 125 NE 40th Street | Oklahoma City, OK 73105 USA | Phone 866-906-2006 | Fax 405-526-2008

enFORCE_TechData
01/31/14